

IC1000+JX



Key Features

Online Networks

Up to 5,000 users

Removable Terminals

LED Diagnostics

Optional TCP/IP

1 or 2 Door Controller

Multi Technology of Badges

Global and Local Reflexes

Dedicated primarily to access control, the IC1000+ is the cost-effective solution for online installations requiring easy programming and real-time supervision. The IC1000+ is suitable for any installation of up to 5,000 users, from single buildings to multiple sites spread over remote locations. Communication can be achieved through TCP/IP, RS485, RS232 or even a modem.

Programming is achieved through our groundbreaking access control software, GuardPoint Pro / Pro Lite, which allows for real-time movements and accessing, alarm setup and management, graphical maps, time zones, security levels, anti-passback, and global and local reflexes.

The installation can be set up within a few minutes, with the double power supply powering both the readers and controllers, together with the electric releases (maglocks, strike locks, etc.). In the event of a power cut, the optional back up battery can ensure hours of full autonomy.

Technical Specifications			
Software Supported	GuardPoint Pro / Pro Lite	Daily Time Zones	99
No. of Doors	2	Weekly Programs	32
No. of Readers	2	Holidays	40
Relay Outputs	3	Special Days	60
Alarm Input	4	Security Levels	Yes
Event History	4,000	Anti-Passback	Yes
Power Supply	12vDC	Lift Management	Yes
Input Current	120mA @ 12vDC	Parking Management	Yes
Input Current (TCPIP)	370mA @ 12vDC	Alarms	Yes
Backup Battery (op.)	12vDC 7.2Ah	Local Reflex	Yes
Dimensions (mm)	110 (H) x 175 (W) x 2 (D)	Global Reflex	Yes
Operating Temperature	-10°C to +55°C	Door Alarms	Yes

IC1000+JX Enclosure			
Dimensions (mm)	270 (H) x 420 (W) x 70 (D)	Low Battery Monitor	Yes
Total Available Current	3.5Amp	AC Failure Monitor	Yes
Lead Acid Battery Load	13.7vDC @ 2A	Tamper Switch	Yes
Regulated Load	12vDC @ 1.5A	Cabinet Lock	Yes
Non-Regulated Load	12vDC @ 2A	Trunking Knocking	20mm
Operating Temperature	-10°C to +55°C	Integrated Charging	Yes

Ordering Information	
Part	Description
IC1000+JX	2 door / 2 reader controller, featuring 4 inputs, 3 outputs and 5,000 users. Housed in a 12vDC 3.5A power-supply cabinet with key-lock and tamper switch.
IC1000IP+JX	2 door / 2 reader controller with onboard TCP/IP, featuring 4 inputs, 3 outputs and 5,000 users. Housed in a 12vDC 3.5A power-supply cabinet, as above.